

Material Safety Data Sheet



Product Name **CHEMDUSTFREE**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name **HEINEMANN ELECTRIC PTY LTD**
Address 821 Springvale Road, Mulgrave, Victoria, AUSTRALIA, 3170
Telephone (03) 9590 3500
Fax (03) 9562 0420
Emergency (03) 9590 3500
Email sales@heinelec.com.au
Web Site http://www.heinemannelectric.com.au

Synonym(s) SC-DF250 - PRODUCT CODE

Use(s) DUST CONTROL • DUST REMOVER • ELECTRONIC CLEANER

MSDS Date 08 Dec 2006

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	3159	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2RE	EPG	2C2

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
1,1,1,2-TETRAFLUOROETHANE (HFC 134A)	C2-H2-F4	811-97-2	>60%

4. FIRST AID MEASURES

Eye Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate for 15 minutes. Seek medical attention.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available.

Skin Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15 minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for 15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.

Ingestion Not considered a potential route of exposure.

Advice to Doctor Treat symptomatically

First Aid Facilities Eye wash facilities and safety shower should be available.

AMBER

Product Name **CHEMDUSTFREE**

5. FIRE FIGHTING MEASURES

Flammability	Non flammable. May evolve toxic gases (fluorides, carbon oxides, hydrocarbons) when heated to decomposition.
Fire and Explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot.
Extinguishing	Use water fog to cool containers from protected area.
Hazchem Code	2RE

6. ACCIDENTAL RELEASE MEASURES

Spillage	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.
-----------------	--

7. STORAGE AND HANDLING

Storage	Store cylinders securely, in separate area in an upright position in cool (<45°C), dry, well ventilated area, removed from heat sources, oxidising agents, alkalis, alkaline earth metals, metal powders & foodstuffs. Ensure cylinders are labelled, protected from physical damage and valves closed when not in use. Make use of old stock first, do not store empty and full cylinders together.
Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.


8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	1,1,1,2-Tetrafluoroethane	ASCC (AUS)	1000	4240	--	--

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE Wear nitrile gloves, safety boots and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	CLEAR COLOURLESS GAS (LIQUEFIED UNDER PRESSURE)	Solubility (Water)	INSOLUBLE
Odour	ETHEREAL ODOUR	Specific Gravity	NOT AVAILABLE
pH	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT AVAILABLE		

AMBER

Product Name **CHEMDUSTFREE**

10. STABILITY AND REACTIVITY

Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), alkalis/ alkali earth metals.
Hazardous Decomposition Products	May evolve toxic gases (fluorides, carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Asphyxiant gas - non irritant. Adverse health effects may result upon exposure at very high levels or with direct contact. Prevent vapour build up and direct eye/skin contact. Over exposure at high levels may result in cardiac arrhythmias (irregular beating or arrest of the heart). Individuals with pre-existing medical conditions (CNS, heart, lungs, kidneys) may have increased susceptibility.
Eye	Non irritant. However, direct contact with evaporating liquid may result in severe cold burns with possible permanent damage.
Inhalation	Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.
Skin	Non irritant. However, direct contact with the liquefied material or escaping compressed gas may cause frostbite injury.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	1,1,1,2-TETRAFLUOROETHANE (HFC 134A) (811-97-2) LC50 (Inhalation): 1500 g/m ³ /4 hour (rat) TCLo (Inhalation): 5000 ppm/6 hour/2 years intermittently (rat)

12. ECOLOGICAL INFORMATION

Environment	Global warming has been predicted as a potential consequence of the emission of this product.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.
------------------	--



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R 134a)				
UN No.	3159	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2RE	EPG	2C2

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information	ASPHYXIAN GASES: Asphyxiant gases may displace oxygen, leading to oxygen deficiency. Where oxygen content is low, effects may include: 12-16% oxygen: increased breathing/ pulse rate, lack of coordination; 10-14%: mental disturbance, fatigue, breathing stress; 6-10%: vomiting, collapse and possible unconsciousness; 0-6%: convulsions, respiratory collapse and death.
-------------------------------	--

Product Name CHEMDUSTFREE

ASPHYXIANTS (1): When present in the atmospheres in high concentrations, asphyxiants reduce the oxygen concentration by displacement. Atmospheres deficient in oxygen do not provide adequate sensory warning of danger and most simple asphyxiants are odourless. Therefore it is not appropriate to recommend an exposure standard for each asphyxiant, but to maintain oxygen concentrations. However, some asphyxiants may be given an exposure standard due to the potential for narcotic effects at high concentrations or an explosion hazard.

ASPHYXIANTS (2): There is a significant hazard associated with workers entering poorly ventilated areas (eg. tanks) where oxygen may be deficient. An air supplied breathing apparatus may be required if adequate ventilation is not ensured.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all Chem Alert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

AMBER

Product Name **CHEMDUSTFREE**

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

MSDS Date: 08 Dec 2006

End of Report